15. (Once Amended) A master information carrier used for recording information signals on a magnetic recording medium, comprising a non-magnetic substrate; a pattern of a ferromagnetic film which is disposed on the surface of the non-magnetic substrate, the pattern being disposed in the track length direction so as to correspond to an arrangement of the information signals; and a non-magnetic solid material filled in portions between respective neighboring ferromagnetic film areas composing the pattern,

wherein the ferromagnetic film comprises a material selected from the group consisting of Co, Fe, and an alloy comprising Co or Fe as the main component, and the non-magnetic solid material is selected from the group consisting of SiO<sub>2</sub>, Al<sub>2</sub>O<sub>3</sub>, Cu, Ag and an alloy comprising Cu or Ag as the main component.

16. (Once Amended) A master information carrier used for recording information signals on a magnetic recording medium, comprising a non-magnetic substrate having an embossed surface that forms a pattern of recessed portions corresponding to an arrangement of the information signals; and a ferromagnetic film filled in the recessed portions of the pattern,

wherein the ferromagnetic film comprises a material selected from the group consisting of Co, Fe, and an alloy comprising Co or Fe as the main component and the non-magnetic substrate comprises a material selected from the group consisting of SiO<sub>2</sub>, Al<sub>2</sub>O<sub>3</sub>, Si, and C.

## Please add new claim 22 as follows:

Mew) A master information carrier used for recording information signals on a magnetic recording medium, comprising a non-magnetic substrate; a pattern of ferromagnetic film which is disposed on the surface of the non-magnetic substrate, the pattern being disposed in the track-length-direction so as to correspond to an arrangement of the information signals; and a non-magnetic solid materials filled in portions between the respective neighboring ferromagnetic films areas composing the pattern,

wherein the ferromagnetic film comprises a material selected from the group consisting of Co, Fe, and an alloy comprising Co or Fe as the main component, and the non-magnetic solid material comprises a polymer material.